

S-2500 FLUID END ASSEMBLY VALVE-OVER-VALVE QUINTUPLEX

FIELD-PROVEN SERVICE.

PREMIUM MATERIALS AT A FRIENDLY PRICE.

Furion's S-2500 Quintuplex is manufactured from Italian 15-5 stainless steel at our API Q1 manufacturing facility and dressed with premium internals for maximum performance.

You won't find a better cost per pumping hour in the market.



SPECIFICATIONS

Centers:	10"
Stroke:	8"
Weight:	4800 lbs
Displacement per Rev:	2.75 gal (4.5") 2.18 gal (4")
Maximum PSI:	12,600 PSI (4.5") 15,000 PSI (4")

COMPATIBILITY:
QWS-2500 / SD
GD-2500Q
F/J-2510

Calculations are based on 90% mechanical efficiency and 100% volumetric efficiency.

Contact Furion engineering for applications demanding pressures over 15,000 PSI.

4" & 4.5" UNITS IN STOCK



FEATURES

Field Proven Technology

A tried-and-true design. Our units are operating in every major US basin year-round.

Low-Cost per Pumping Hour

Our units are capable of reaching 1000+ pumping hours at market leading price point.

Top Notch Material

Premium Stainless-Steel cylinder dressed with bonded valves, gold packing, and Q1 machined components.

OPTIONS

Surface Finishing

Choose from bare stainless-steel, primed, or painted to your specification.

Discharge Flanges

Select from various configurations using 2" 1502, 3" 1502, and blind flanges.